



ULTRASONIC CLEANER

An Ultrasonic Cleaner quickly and gently removes sample residues from test sieves, without damaging the mesh material.

An ultrasonic cleaner not only increases the lifetime of test sieves, it is especially recommended for small apertures. For reliable results, cleaning is recommended after each analysis.

PRODUCT ADVANTAGES

- | Has been specially designed for cleaning test sieves
- | Suitable for general laboratory use.
- | Easy to operate and extremely efficient to use

ULTRASONIC CLEANER

TECHNICAL DATA

Application	cleaning, dispersion, degassing
Batch size / feed quantity*	1 sieve 200 x 50 mm, 8" x 2"
Time setting	0 - 15 min
Container volume	5.7 l
Oscillating tank Ø x H / W x H x D	24.5 x 13 cm
HF continuous maximum output	35 kHz, 2 x 240 W
Electrical supply data	different voltages available
Power connection	1-phase
Ø x H / W x H x D	260 x 260 mm
Net weight	~ 5 kg

www.endecotts.com/sieves

ORDER DATA

ULTRASONIC CLEANER

suitable for 200 mm / 8" diameter sieves

ZMULT-ULT0 Ultrasonic cleaner, 220-240 V, 50/60 Hz, UK plug

ZMULT-ULT0/2 Ultrasonic cleaner, 230 V, 50 Hz, Euro plug

ZMULT-ULT0/1 Ultrasonic cleaner, 110/120 V, 60 Hz, USA plug

ACCESSORIES

ZMULT-FLU1 Ultrasonic cleaning Fluid